

Ecobus Window Blinds  
Actuator  
2/6A A-N  
2x window blind actuator 6A AC



## Product Information

### Application

To control two independent groups with a maximum of 2 blind motors each – UP, DOWN and stepped blind settings; OPEN and CLOSED. The device needs no additional power supply. The bus is connected via the bus connection terminal.

The following functions can be set according to the application selected using the configuration software:

- Time paused when changing direction
- Monitor period for wind sensor
- Safety on wind alarm trigger
- Blind run time
- Impulse time for setting blinds

Power supply via the Ecobus EIB.

### Technical Properties

Outputs	2 x 2, change-over contacts
Nominal voltage	230 V AC + 10 / – 15%, 50 Hz
Switching current	6 A
User and display components	LED and button for input of physical address
Protection method	IP 20 in accordance with EN 60 529
Operating temperature range	-5°C to +45°C
Connection	1 screw terminal (L) per group 2 x 2 screw terminals (UP, DOWN)
Connection cross section	fine wire 0.5 – 2.5 mm <sup>2</sup> , single wire 0.5 -4.0 mm <sup>2</sup>
Ecobus EIB	
Bus connection terminal	supplied.

### General Properties

Assembly	35 mm rail, DIN EN 50 022
Dimensions (H x W X D)	90 x 72 x 64 mm
Assembled depth / width	68 mm / 4 modules at 18 mm

Article No.	Dimensions	Weight	Packaging Unit
	Module width	kg/unit	Unit
301 009	4	0.24	1