



Product Information

Application

Used to control four independent window blind drivers – UP and DOWN and stepped blind control OPEN and CLOSED. The device needs no additional power supply.

The bus is connected via the bus connection terminal.

The following functions can be set according to the application selected using the configuration software:

- Time paused when changing direction
- Monitor period for wind sensor
- Safety on wind alarm trigger
- Blind run time
- Impulse time for setting blinds
- Ventilation flap operation
- Set to position (2 presets per channel)

Power supply via the Ecobus EIB.

Technical Properties

Outputs	4 independent channels
Nominal voltage	230 V AC +/- 10 %, 50 Hz
Switching current	6 A
User and display components	LED and button for input of physical address
Protection method	IP 20 in accordance with EN 60 529
Operating temperature range	-5°C to +45°C
Connection	1 screw terminal (L) for 2 channels per channel 2 screw terminals (UP, DOWN)
Connection cross section	fine wire 0.2 - 2.5 mm ² single wire 0.2 -4.0 mm ²
Ecobus EIB	
Bus connection terminal	supplied.

General Properties

Assembly	35mm rail, DIN EN 50 022
Dimensions (H x W x D)	90 x 72 x 64 mm
Insert depth	68 mm / 4 modules at 18 mm

Article No.	Dimensions	Weight	Packaging Unit
301 010	Module width 4	kg/unit 0.25	Unit 1