



Fig. 1:
Ecobus Combi Vamp
5 x Power



Fig. 2:
Ecobus Combi Vamp EIB
5 x Power + EIB Bus



Fig. 3:
Ecobus Combi Vamp
5 x Power + Bus

Product information

Application

For permanently connecting the Ecobus Combi cable in dry areas without the need to remove cable sheathing.

General Properties

Housing	Polyamide 6,6
Slider	Polyamide 6,6, glass-fibre reinforced, black
Cap	Polycarbonate, transparent
Power current screw	Silver-plated brass, for posidrive no. 2 screwdriver
Bus screw	Galvanised brass, for normal no. 2 screwdriver
Test Specifications	IEC 998-1, IEC 998-2-3, Provisional IEC 61535 and VDE 0628
Housing	Flammability according to UL Standard 94: V-2
Slider and Cap	Flammability according to UL Standard 94: V0
Slider	Glass-fibre: 25%
Connection	Output on side with confusion-free jacks

Further Information

For the correct jack for 300283, see page 214.
For the correct combination jack for 300284, see page 216.
For the correct combination jack for 300351, see page 216.

See fig. 1: Ecobus Combi Vamp

Article no.	For nom. cross section	Weight	Dimensions	Fire load	Packaging Unit
	n x mm ²	g/unit	app. mm	kWh/unit	pcs.
300 283	5 x 2.5	64.5	57.5 x 54 x 25.7	0.271	50

See fig. 2: Ecobus Combi Vamp EIB / For EIB applications

Article no.	For nom. cross section	Weight	Dimensions	Fire load	Packaging Unit
	n x mm ²	g/unit	app. mm	kWh/unit	pcs.
300 284	5 x 2.5 + 2 x 0.5	82	57.5 x 79 x 25.7	0.4	50

See fig. 3: Ecobus Combi Vamp

Article no.	For nom. cross section	Weight	Dimensions	Fire load	Packaging Unit
	n x mm ²	g/unit	app. mm	kWh/unit	pcs.
300 351	5 x 2.5 + 2 x 0.5	82	57.5 x 79 x 25.7	0.4	50