



Fig. 1:  
Ecobus Data Vamp EIB  
EIB Bus



Fig. 2:  
Ecobus Data Vamp  
Bus



Fig. 3:  
Ecobus Data Vamp Quick  
EIB Bus

**Product information**

**Application**

For permanently connecting the Ecobus Data cable in dry areas without need to remove cable sheathing.

**General Properties**

Housing	Polyamide 6,6, glass-fibre reinforced, black/green
Slider	Polyamide 6,6, glass-fibre reinforced, black
Cap	Polycarbonate, transparent
Bus screw	Galvanised brass, for normal no. 2 screwdriver
Test Specifications	IEC 60 998-1, IEC 60 998-2-3 and VDE 0628

Housing, slider and cap	Flammability in accordance with UL Standard 94: VO
	Halogen-free
Housing/Slider	Glass-fibre: 25%
Connection	Output with easy to identify jack or snap-clip connection (art. No. 300 303).

Housing	Polyamide 6,6, glass-fibre reinforced, black/green
Slider	Polyamide 6,6, glass-fibre reinforced, black
Cap	Polycarbonate, transparent
Bus screw	Galvanised brass, for normal no. 2 screwdriver
Test Specifications	IEC 60 998-1, IEC 60 998-2-3 and VDE 0628

**Further Information**

For the correct jack for 300286, see page 216. For the correct jack for 300353, see page 216.

See fig. 1: Ecobus Data Vamp / For EIB applications

Article no.	For nom. cross section	Weight	Dimensions	Fire load	Packaging Unit
	n x mm <sup>2</sup>	g/unit	app. mm	kWh/unit	pcs.
300 286	2 x 0.5	12.8	47 x 23.5 x 18	0.08	50

See fig. 2: Ecobus Data Vamp / For Ecobus Data

Article no.	For nom. cross section	Weight	Dimensions	Fire load	Packaging Unit
	n x mm <sup>2</sup>	g/unit	app. mm	kWh/unit	pcs.
300 353	2 x 0.5	12.8	47 x 23.5 x 18	0.08	50

See fig. 3: Ecobus Data Vamp Quick / For Ecobus Data

Article no.	For nom. cross section	Weight	Dimensions	Fire load	Packaging Unit
	n x mm <sup>2</sup>	g/unit	app. mm	kWh/unit	pcs.
300 303	2 x 0.5	12.8	47 x 23.5 x 18	0.08	50