



Fig. 1:
Ecobus Power Vamp
3 x Power



Fig. 2:
Ecobus Power Vamp
5 x Power



Fig. 3:
Ecobus Power Vamp-S
5 x Power

Product information

Application

For permanently connecting the Ecobus Power cable in dry areas without the need to remove cable sheathing.

General Properties

Housing	Polyamide 6,6, phase L1 light grey, phase L2 dark grey, Phase L3 black
Slider	Polyamide 6,6, glass-fibre reinforced, black
Cap	Polycarbonate, transparent
Power current screw	Silver-plated brass, for posidrive no. 2 screwdriver
Test Specifications	IEC 998-1, IEC 998-2-3, Provisional IEC 61535 and VDE 0628
Housing	Flammability according to UL Standard 94: V-2
Slider and Cap	Flammability according to UL Standard 94: V0
	Halogen-free
Slider	Glass-fibre: 25%
Connection	Output with non exchangeable jacks or screwable for article no 301 076 Ecobus Combi Vamp-S

Further Information

Article 301075

One packaging unit contains 48 items, 16 each of L1, L2 and L3. The phases can be distributed evenly by corresponding assembly.

For the correct combination jack for 301 075, see page 214.
For the correct combination jack for 301 077, see page 216.

See fig. 1: Ecobus Power Vamp / (L1/L2/L3)

Article no.	For nom. cross section	Weight	Dimensions	Fire load	Packaging Unit
	n x mm ²	g/unit	app. mm	kWh/unit	pcs.
301 075	3 x 2.5	40	57.5 x 34.5 x 25.7	0.178	48

See fig. 2: Ecobus Power Vamp

Article no.	For nom. cross section	Weight	Dimensions	Fire load	Packaging Unit
	n x mm ²	g/unit	app. mm	kWh/unit	pcs.
301 077	5 x 2.5	64.5	57.5 x 54 x 25.7	0.271	50

See fig. 3: Ecobus Power Vamp-S

Article no.	For nom. cross section	Weight	Dimensions	Fire load	Packaging Unit
	n x mm ²	g/unit	app. mm	kWh/unit	pcs.
301 076	5 x 2.5	60	53 x 41 x 39	0.329	50