pyrosys®

Preventive fire protection

Cable duct I30 (Hermannkanal)

HSK I 30/1200

Dätwyler

Product information

Application

Cable duct system for exposure to fire from inside to outside, for prevention of fire propagation on cabling systems in floors and stairwells in accordance with MLAR 03/2000.
Installation with screw set directly onto multi cable support (Hermann clamp). Spacing of fixation 600 mm.

Technical Data

Material	Light construction fire protection plate
Colour	White, impregnated
Approvals	ABP No.: P-3015 / 6930 – MPA BS
Dimensions	Outside (wxh): 170x195
	Inside: 120x170

Cable duct I30 (Hermannkanal) with installation set, multi cable support (Hermann clamp) and fire safety plug KDN 30mm.
Drill and installation tool are not included. Recommended drill SDS 1, recommended installation tool SWM-SM 50.

Article No.	Type	Info	Packaging
301 158	Pyrosys HSK I 30/1200	L= 1.200 mm	1 Set
301 159	Pyrosys HSK I 30/600	L= 600 mm	1 Set
301 160	Pyrosys HSK I 30/400	L= 400 mm	1 Set
301 161	Pyrosys HSK I 30/B90	90° right-hand angle	1 Set
301 164	Pyrosys HSK I 30/B90	90° left-hand angle	1 Set
301 162	Pyrosys HSK I 30/B45	45° right-hand angle	1 Set
301 163	Pyrosys HSK I 30/B45	45° left-hand angle	1 Set
301 167	Pyrosys HSK I 30/Cross		1 Set
301 166	Pyrosys HSK I 30/T joint		1 Set
301 157	Pyrosys HSK I 30/End part		1 Piece

Accessories

Multi cable support (Hermann clamp) for I30 duct (Hermannkanal)

Article No.	Type	Info	Packaging
300 964	Pyrosys SHUD	Hermann clamp	10

Fire protection paint

Article No.	Type	Info	Packaging
300 465	Pyrosys SZ	Fire protection paint	25 kg plastic bucket

Fire protection filler

Article No.	Type	Info	Packaging
300 467	Pyrosys SP K	Fire protection filler	12 cartridges