



Identification sign

## Product Information

### Application

used to form a bulkhead for cable wall and ceiling penetration, against the effects of fire for a period of 90 minutes in accordance with DIN 4102-9 (fire resistance class S90).

Article No.	Bulkhead	Application	Info
300 470	Fire protection plug Pyrosys TS90	For provision of a round S90 bulkhead in ceilings and walls in accordance with DIN 4102-9	Packaging comprises 20 pieces For bore holes up to 65 mm dry and dust-free assembly, problem free installation
300 471	Fire protection plug Pyrosys TS90	For provision of a round S90 bulkhead in ceilings and walls in accordance with DIN 4102-9	Packaging comprises 20 pieces For bore holes up to 78 mm dry and dust-free assembly, problem free installation
300 472	Fire protection plug Pyrosys TS90	For provision of a round S90 bulkhead in ceilings and walls in accordance with DIN 4102-9	Packaging comprises 20 pieces For bore holes up to 108 mm dry and dust-free assembly, problem free installation
300 473	Fire protection plug Pyrosys TS90	For provision of a round S90 bulkhead in ceilings and walls in accordance with DIN 4102-9	Packaging comprises 20 pieces For bore holes up to 123 mm dry and dust-free assembly, problem free installation
300 474	Fire protection plug Pyrosys TS90	For provision of a round S90 bulkhead in ceilings and walls in accordance with DIN 4102-9	Packaging comprises 20 pieces For bore holes up to 135 mm dry and dust-free assembly, problem free installation
300 475	Fire protection plug Pyrosys TS90	For provision of a round S90 bulkhead in ceilings and walls in accordance with DIN 4102-9	Packaging comprises 20 pieces For bore holes up to 165 mm dry and dust-free assembly, problem free installation
300 476	Fire protection plug Pyrosys TS90	For provision of a round S90 bulkhead in ceilings and walls in accordance with DIN 4102-9	Packaging comprises 20 pieces For bore holes up to 200 mm dry and dust-free assembly, problem free installation
300 477	Fire protection block Pyrosys TS90	For closing gaps and spandrels and wall soffits	Set consists of 12 cartridges 310 ml cartridge, white
300 478	Identification sign Fire protection plug Fire protection brick	For permanent identification of a cable bulkhead in accordance with DIN 4102-9	Set consists of 10 Identification signs